

Fire detection  
**Mounting material for linear heat  
 detectors**  
 (detector wire)




Data sheet no.B007E

Rev. 004 of 2008-08-20

Fasteners should typically be spaced every 1.5-3m (5-10 feet), or as may be necessary to prevent the wire from excessive sagging which puts undue stress on the wire at the fastening points. Improper installation and fastening may also subject the Detector to physical damage in some process areas or interactive applications, such as rack storage facilities.

Picture / Item no. / Description	Unit	Packing unit
----------------------------------	------	--------------

Universal Mounting accessories

	Clip WAW for mounting at ceilings and walls as well as for corners (turns) Operating temperature -40°C to 88°C		
	100531	Mounting clip for WLM, Nylon, WAW	Pieces 100
	100532	Mounting clip for WLM, Polypropylene, WAW	Pieces 100
	Clip for main use between turns or corners being mounted by WAW Clips		
	100547	Mounting clip for WLM, Stahl, OHS, Screw hole Ø 4.8mm	Pieces 100
	100533	Mounting clip for WLM, Stahl, OHS, Screw hole Ø 6.4mm	Pieces 100
	Coated beam clamp for inside rooms, beam clamp with clip WAW pre-mounted		
	100534	Beam clamp with WAW clip for WLM, BC	Pieces 100
	Galvanized heavy duty beam clamp with WAW clip pre-mounted, for inside and outside rooms		
	100536	Beam clamp with WAW clip, BC, galvanized beam clamps, Clip: Nylon	Pieces 100
	100535	Beam clamp with WAW clip, BC, galvanized beam clamps, Clip: PP	Pieces 100
	Steel L-bracket, height 17.0 cm, 5 holes for multiple height adjustments, WAW clip pre-mounted		
	100537	L- bracket for WLM, Steel, RMC	Pieces 100
	100538	L- bracket for WLM, Stainless steel, RMC	Pieces 100
	Insulated standoff for mounting WLM-detector wire		
	100585	Standoff, isolated loop (WLM) TR-5G	Pieces 100
	Cable mount for adhesive bonding, for surfaces which do not allow screwing, with bushing for cable ties, use in indoor and outdoor applications, should not be used in hash chemical environments, incl. Cable tie Operating temperature -17°C to 82°C		
	100586	Adhesive bonding plate for WLM, incl. cable tie EMS + PLT1S	Pieces 100

Fire detection  
**Mounting material for linear heat  
 detectors**  
 (detector wire)






Data sheet no.B007E



Rev. 004 of 2008-08-20

Picture / Item no. / Description	Unit	Packing unit
----------------------------------	------	--------------



Cable tray mounting

	Clip for mounting of WLM detector wire at cable trays, Nylon clip with internal spring steel clamp, for profiles of 1.5mm to 6.4mm, easy installation and removal by snap-lock			
	100587	Clip for cable tray mounting of WLM, HPC	Pieces	100
	Mounting clip with WAW clip pre-mounted			
	100540	Cable tray-Caddy for WLM, with Clip, N2, CC-2, for tray material of 1.6 mm to 4.0 mm	Pieces	100
	100541	Cable tray-Caddy for WLM, with Clip, W2, CC-2, for tray material of 4.0 mm to 6.4 mm	Pieces	100
	Cable Tray clip, Spring steel clip with WAW Cable clip pre-mounted. Where excessive vibrations may be encountered the clip can be fixed with hex-screws and hex nuts. Please add an "-S" after the model number (CC-10).			
	100542	Cable tray-Caddy for WLM, with Clip, N10, CC-10, for tray material of 3.2 mm to 6.4 mm	Pieces	100
	100543	Cable tray-Caddy for WLM, with Clip, W10, CC-10, for tray material of 7.9 mm to 12.7 mm	Pieces	100

Mounting on pipes

	Pipe mounting straps for WLM, black weather resistant Nylon, ambient temperature of -40°C to 85°C			
	100545020	Pipe mounting straps, Diameter: 3/4" bis 2" (DN20-50)	Pieces	100
	100545065	Pipe mounting straps, Diameter: 2 1/2" bis 3" (DN65-80)	Pieces	100
	Two single straps for WLM to be mounted on pipes, black weather resistant Nylon, ambient temperature of -40°C to 85°C			
	100545100	Pipe mounting straps, Diameter: 4" bis 6" (DN100-150)	Pieces	100

Fixings for messenger wire

	Eyebolt for messenger wire installation			
	100588	Exebolt, Steel, TR4	Pieces	100
	100589	Eyebolt, Stainless steel, TR4	Pieces	100
	Turnbuckle for messenger wire installation			
	100590	Turnbuckle, Steel, TR-2	Pieces	100
	100591	Turnbuckle, Stainless steel, TR-2	Pieces	100